



EXCELAM-

Large Format Cold Laminator

Q1400COLD/RS
Q1600COLD/RS
Q1600COLD/RS-E
Q1600COMBI/RS



EXCELAM-

Q1400COLD/RS
Q1600COLD/RS
Q1600COLD/RS-E
Q1600COMBI/RS



- ◆ High speed Laminating (Up to 5m/min)
- ◆ Strengthen Main Motor for Drive Torque and its durability
- ◆ Rewinder connected to the powerful main motor
- ◆ Easy to use for outer rewriter tension control
- ◆ Designed for dual film core and stronger unwinder shaft
- ◆ Capable of roller Max Temperature (Up to 150°C)
- ◆ Mounting Up to 13mm
- ◆ Cross Cutter for Limited Web Removal
- ◆ Sub Heating System (Upper Roller) : 1600COMBI/RS
- ◆ Top Rewinder for Release Liner



Laminex-Registered Trade Mark



EXCELAM-

Q1400COLD/RS
Q1600COLD/RS
Q1600COLD/RS-E
Q1600COMBI/RS



Roll Laminator

EXCELAM-Q is the perfect machine to procedure wide range of service in a copy shop environment or as a print Finishing. Ideal for laminating posters, ink-jet prints, leaflets and maps with superb results and for truly professional mounting up to 13mm GMP LAMIFOAM(Foamboard).

Super laminating results on wide ranges of Cold laminating films from 25, 50 micron GMP Crystalex Film (Polyester Base Cold Film), including 75,100 micron GMP Pronex Cold UV Film (Soft Touch Cold Film). Features include variable speed and pressure adjust handle, for laminating thickness and pressure, mounting thickness setting.



Specifications

Model Name	EXCELAM-Q1400COLD/RS	EXCELAM-Q1600COLD/RS	EXCELAM-Q1600COLD/RS-E	EXCELAM-Q1600COMBI/RS
Laminating Speed	5m/min	5m/min	5m/min	5m/min
Laminating Width	1400mm	1600mm	1600mm	1600mm
Laminating Films	75mic-500mic	75mic-500mic	75mic-500mic	25mic-500mic
Thickness of substrate(Paper)	80g/m ² ~ 350g/m ²	80g/m ² ~ 350g/m ²	80g/m ² ~ 350g/m ²	80g/m ² ~ 350g/m ²
Thickness Mount	13mm	13mm	13mm	13mm
Power Requirements	AC 220V-240V, 50/60Hz	AC 220V-240V, 50/60Hz	AC 220V-240V, 50/60Hz	AC 220V-240V, 50/60Hz
Power Consumption	100W, 0.4A	100W, 0.4A	100W, 0.4A	2000W, 8.3A
Warm up Time	-	-	-	5 minutes (40°C)
Heating System	-	-	-	Hot Roller Internal Infrared Heater
Operating Temperature	-	-	-	150°C Max.
Speed Control	Knob & Volume	Knob & Volume	Knob & Volume	Key Pad
Temperature Control	-	-	-	Key Pad
Pressure Adjustment	Manual (lever, 6-preset)	Manual (lever, 6-preset)	Manual (lever, 6-preset)	Manual (lever, 6-preset)
Film Core	19-77Dual	19-77Dual	19-77Dual	19-77Dual
Dimensions(WxLxH)	1640 x 750 x 1200mm	1840x 750 x 1200mm	1840x 750 x 1200mm	1840x 750 x 1200mm
Type of Main Motor	DC W-Geard Motor /36V80	DC W-Geard Motor /36V80	DC W-Geard Motor /36V80	DC W-Geard Motor /36V80
Type of Rewinder Motor	Link to Main Motor	Link to Main Motor	Link to Main Motor	Link to Main Motor

Copyright GMP 2003. All rights reserved. Reproduction by any means of any image in this catalogue is prohibited without the prior consent of GMP and its authorized agent

GMP reserves the right to after change specifications without prior notice.

- * Chromonex® : PP and PET composite Film
- * Photonex® : Heat Seal Laminating utilizing PVC material Film
- * Polynex® : Heat Seal Laminating utilizing OPP material Film
- * Micronex® : Heat Seal Laminating utilizing ultra thin dry overcoating Film